

RLK8-800B4-NVR-Kit-NVR-Specifications

| | Model | RLN8-410 |
|---------------------------|-------------------------------|--|
| Video/Audio Input | IP Video Input | PoE IP Camera x 8 |
| | Audio Input | Cameras with Built-in Mic |
| Video/Audio Output | HDMI Output | 3840x2160, 1920x1080, 1440x900, 1280x1024, 1280x800, 1280x720, 1024x768 |
| | VGA Output | 1920x1080, 1440x900, 1280x1024, 1280x800, 1280x720, 1024x768 |
| | Audio output | 1CH RCA |
| Decoding | Live View/Playback Resolution | 3840x2160, 2560x1920, 2560x1440, 2048x1536, 2304x1296, 1080p, 720p |
| | Video Format | H.264 |
| | Synchronous Playback | Up to 4 Channels |
| HDD | SATA Devices | 1 x 2TB SATA HDD |
| | Maximum Capacity | 8TB (Maximum 4TB HDD/Port) |
| | External HDD | 1 x eSATA |
| External Interface | USB Interface | 2 x USB 2.0 |
| | Network Interface | RJ45,10M/100M Ethernet, 8 Network Ports for IP camera, 1 Giga Network Port for LAN/WAN |
| PoE | Interface | 8 Independent 100 Mbps PoE Network Interfaces |
| | Max. Power Consumption | 25W |
| | Supported Standard | IEEE 802.3at |
| Network | Network Protocol | HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP |
| | Browser Supported | IE, Firefox, Chrome |
| | OS Supported | PC: Windows, Mac OS; SmartPhone: iOS, Android |
| | Max. User Access | 20 Users |
| General | Power Supply | DC 48V/2A |
| | Power Consumption | <10W (Without HDD&PoE) |
| | Working Environment | Temperature: -10℃~+45℃ (14°F~113°F); Humidity: 10%~90% |
| | Dimensions (mm) | 260(W) x 41(H) x 230(D) |
| | Weight (w/o HDD) | 1.2 kg |