

Reolink-Go-Plus-Camera-Specifications

Model	Reolink Go Plus	
Video & Audio	Image Sensor	1/3" CMOS Sensor
	Video Resolution	2560 x 1440 (4.0 megapixel) at 15 frames/sec
	Video Format	H.265
	Field of View	Fixed lens, horizontal: 95°; vertical: 52°
	Infrared Night Vision	up to 10 meters (33ft) (LED: 6pcs/14mil/850nm)
	Digital Zoom	16x digital zoom
	Audio	Two-way audio
PIR Detection & Alerts	Smart Alarm	PIR detection/person detection/vehicle detection
	PIR Detecting Distance	Adjustable up to 10m (33 ft)
	PIR Detecting Angle	120° horizontal
	Audio Alert	Customized verbal alerts
	Recording	Motion triggered recording
	Other Alerts	Instant email alerts and push notifications
3G/4G	Frequency Bands	Europe Version: LTE FDD: B1/B3/B5/B7/B8/B20 WCDMA: B1/B5/B8
		America Version: LTE FDD: B2/B4/B12 WCDMA: B2/B4/B5
		Australia Version: LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8
	Transmission Data	LTE FDD: Max. 10Mbps(DL), Max. 5Mbps(UL)
		LTE TDD: Max. 8.96Mbps(DL), Max. 3.1Mbps(UL)
HSPA+: Max. 42Mbps(DL), Max. 5.76Mbps(UL)		
UMTS: Max. 384Kbps(DL), Max. 384Kbps(UL)		
Power	Battery	7800mAh rechargeable battery (Battery life varies based on settings, usage & temperature.)
	Solar	Reolink Solar Panel
	DC Power	5V/2A USB power adaptor
Storage	Local Storage	Supports up to 128GB micro SD card
	Cloud Storage	Supports Reolink Cloud (available in some countries)
Smart Home	Smart Home	Works with Google Assistant
Working Environment	Operating Temperature	-10 to 55° C (14° to 131° F)
	Weather Resistance	IP65 weatherproof
Size & Weight	Size	Φ75 x 194mm (2.95 x 7.63 in)
	Weight (Battery Included)	450g (15.9oz)
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .