Reolink Innovation Limited

Picture			
Model		**Keen Ranger PT**	
Video & Audio	Image Sensor	1/3" CMOS Sensor	
	Video Resolution	2560 x 1440 (4Megapixels)@15FPS	
	Video Format	H.265	
	Lens	f = 2.8mm fixed, F1.6	
	Field of View	Horizontal: 95°, Vertical: 57°, Diagonal：115°	
	Infrared Night Vision	Up to 10 Meters (33ft) (LED: 12pcs/14mil/940nm)	
	Digital Zoom	16x digital zoom	
	Audio	Two-way audio	
PIR Detection & Alerts	Smart Alarm	PIR Detection/Human Detection/Animal Detection	
	PIR Detecting Distance	Adjustable up to 10m (33 ft)	
	PIR Detecting Angle	120° horizontal	
	Audio Alert	Customized verbal alerts	
	Recording	Motion Triggered Recording	
	Other Alerts	Instant email alerts and push notifications	
3G/4G	Frequency Bands	Europe	LTE FDD: B1/B3/B5/B7/B8/B20	
			WCDMA: B1/B5/B8	
		America	LTE FDD: B2/B4/B12	
			WCDMA: B2/B4/B5	
		Australia	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28	
			LTE TDD: B40	
			WCDMA: B1/B2/B5/B8	
	Transmission Data		LTE FDD: Max 10Mbps(DL), Max 5Mbps(UL)	
			LTE TDD: Max 8.96Mbps(DL), Max 3.1Mbps(UL)	
			HSPA+: Max 42Mbps(DL), Max 5.76Mbps(UL)	
			UMTS: Max 384Kbps(DL), Max 384Kbps(UL)	
Other Features	Add Markers	Yes	
Power	Battery	6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature)	
	Solar	Reolink Solar Panel	
	DC Power	5V/2A USB power adaptor	
Storage	Local Storage	Supports up to 128GB micro SD card	
	Cloud Storage	Supports Reolink Cloud	
Smart Home	Work with	Google Assistant	
Working Environment	Operating Temperature	-10 to 55° C (14° to 131° F)	
	Waterproof	Support	
Size & Weight	Dimension	Φ98 x 112mm (Φ3.7 x 4.4 in)	
	Weight (Battery included)	485 g (17.1 oz)	
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/	