

Reolink-Floodlight-PoE-Specifications		
	Model	Reolink Floodlight PoE
<b>General</b>	Light	40pcs, 18W, 4200K, 2000lm
	Indicator light	Support
	PIR	8m
	CDS	Support
<b>Power</b>	POE	IEEE 802.3at, 48V Active
	DC Power	DC 12.0V=2A, <25W
<b>Interface</b>	Power	DC power port
	System	Reset Button
	Ethernet	One 10M/100Mbps RJ45
	Audio	Built-in Speaker( can only be triggered by link device)
<b>Software Features</b>	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	PIR
	Maximal User Access	10 Users (1 admin account & 9 user accounts)
	Work with	Google Assistant
<b>Working Environment</b>	Temperature	Operating Temperature: -10°C~+55°C (14°F~131°F)
	Humidity	Operating Humidity: 10% ~ 90%
	Waterproof	IP 65
<b>Size &amp; Weight</b>	Dimension	216X118X160mm
	Weight	635g
<b>Warranty</b>	Limited Warranty <sup>Ⓜ</sup>	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a> <sup>Ⓜ</sup>