

Reolink-TrackMix-LTE-Plus-Camera-Specifications		
	Model	Reolink TrackMix LTE Plus + Reolink Solar Panel Plus
Video & Audio	Image Sensor	1/3" CMOS Sensor
	Video Resolution	Up to 2560 x 1440 (4 megapixels) @15FPS
	Lens	f=2.8mm@F=1.6, f=8mm@F=1.6
	Video Compression	H.264, H.265
	Field of View	Horizontal: 96°-38° Vertical: 55°-21°
	Zoom	6X hybrid zoom
	Infrared Night Vision	Up to 30 meters (100ft); LED: 2pcs/2W/850nm
	Color Night Vision	Spotlight: 1pcs/6500K/450 lumens
Interfaces	Audio	Two-way audio
	Power	Four-core aviation connector
	System	Reset button
	Storage	MicroSD card slot (Max. 256GB)
	Network	Nano SIM card slot
Pan&Tilt	Audio	Built-in microphone and speaker
	Pan &Tilt	Pan: 355°; Tilt: 90° (PT speed is configurable)
	Preset Points	Supports 1 guard position & up to 32 preset positions
3G/4G	Auto Tracking	Support
	Frequency Bands	• Europe: LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8
		• America: LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71
Australia: LTE FDD: B1/B3/B5/B7/B8/B28 WCDMA: B1/B5/B8		
Software	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	PIR detection; motion detection; person detection; vehicle detection; animal detection
	Recording Modes	Motion-triggered recording (default); scheduled recording, 24/7 recording
	Work with	Google Assistant; Reolink Cloud
Working Environment	Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)
	Humidity	Operating humidity: 20% ~ 85%
	Waterproof	IP65
Solar Panel	Max. Power	66W
Battery	Battery Capacity	155Wh
	Battery Life	A full charge will get the camera ready for 48-hour non-stop recording.
	Built-In Heater	Warm up the battery when temperature is lower than 3°C.
Size & Weight	Dimensions	Camera: 228*147*129mm; Solar Panel+Bracket: 560*700*714mm
	Weight	Camera: 1.4kg ; solar panel+bracket: 10.4kg
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .